

**AT-B series**  
AUTO LEVEL

**TOPCON**

# AT-B series

AUTO LEVEL



**Durable, Dependable,  
High Value Auto Levels**

- 3 MODELS - 32X, 28X, AND 24X MAGNIFICATIONS
- RAPID, ACCURATE, AND STABLE AUTOMATIC COMPENSATION
- ULTRA-SHORT 20CM (7.9 IN.) FOCUSING
- ALL-WEATHER DEPENDABILITY
- CLAMPLESS, ENDLESS FINE HORIZONTAL ADJUSTMENTS

## AT-B2

High-precision model



Magnification <b>32x</b>	Objective Aperture <b>42mm</b>	Accuracy <b>0.7mm</b>
Minimum Focus <b>20cm</b>	Protection <b>IPX6</b>	Weight <b>1.85kg</b>

## AT-B3

Versatile model for surveying,  
engineering and construction



Magnification <b>28x</b>	Objective Aperture <b>36mm</b>	Accuracy <b>1.5mm</b>
Minimum Focus <b>20cm</b>	Protection <b>IPX6</b>	Weight <b>1.7kg</b>

## AT-B4

Economical model for  
engineering and construction



Magnification <b>24x</b>	Objective Aperture <b>32mm</b>	Accuracy <b>2.0mm</b>
Minimum Focus <b>20cm</b>	Protection <b>IPX6</b>	Weight <b>1.7kg</b>



## Rapid, Stable, and Durable Compensator

The compensator of AT-B series incorporates four suspension wires made of super-high-tensile metal that features minimal thermal expansion coefficient, providing unmatched durability and accuracy. Finely tuned magnetic damping system quickly levels and stabilizes the line of sight despite the fine vibrations present when working near heavy equipment or busy roadways.



## 20cm (7.9 in.) - Ultra-Short Minimum Focus

The AT-B series can focus on objects at 20cm (7.9 in.) in front of the telescope. This feature dramatically facilitates the works in confined spaces.

## Horizontal Circle for Angle Measurement

Horizontal angles can be directly read in 1° or 1gon units. Free rotation feature allows you to read any angle from zero. The circle is covered for protection against dirt and scratch. The readout window is located below the eyepiece for quick reading.



## All-Weather Dependability

With the IPx6 rating, the instrument is protected against powerful water jets from all directions, meaning the AT-B series withstands a sudden shower or torrential rainfall. The advanced protection design also deters clouding or condensation inside the telescope.

**It's time.**

### TOPCON CORPORATION

75-1 Hasunuma-cho, Itabashi-ku, Tokyo 174-8580, Japan  
Phone: (+81)3-3558-2993 Fax: (+81)3-3960-4214  
www.topcon.co.jp

**TOPCON SOKKIA INDIA PVT. LTD.**  
C-25, GROUND FLOOR, SECTOR-8,  
NOIDA, U.P. - 201 301  
www.topconsokkia.ind.in

## AT-B series SPECIFICATIONS

	AT-B2	AT-B3	AT-B4
<b>Telescope</b>			
Length	215mm (8.46 in.)		
Magnification	32X	28X	24X
Objective Aperture	42mm (1.65 in.)	36mm (1.42 in.)	32mm (1.26 in.)
Resolving Power	3"	3.5"	4"
Field of View (at 100m/328ft.)	1°20' (2.3m / 7.5ft.)	1°25' (2.5m / 8.2ft.)	
Minimum Focus	0.2m (7.9 in.) from end of telescope 0.3m (1ft.) from instrument center		
Image	Erect		
Stadia Constant	0		
Stadia Ratio	100		
Focusing Knob	2-speed	1-speed	
Sighting Aid	Peep Sight		Gun Sight
<b>Accuracy (1km double run leveling)</b>			
Without Micrometer	0.7mm (0.03 in.)	1.5mm (0.06 in.)	2.0mm (0.08 in.)
With Micrometer	0.5mm (0.02 in.)	n/a	
<b>Compensator</b>			
Type	Pendulum compensator with magnetic damping system		
Setting Accuracy	0.3"	0.5"	
Working Range	±15'		
<b>Circular Level</b>			
Sensitivity	10' / 2mm		
<b>Horizontal Circle</b>			
Diameter	103mm (4.1 in.)		
Minimum Division	1° / 1gon		
<b>General</b>			
Water Resistance	IPX6 (IEC 60529:2001)		
Operating Temperature	-20°C to +50°C (-4°F to +122°F)		
Size	Width	130mm (5.12 in.)	
	Length	215mm (8.46 in.)	
	Height	140mm (5.51 in.)	135mm (5.31 in.)
Weight	1.85kg (4.1 lbs.)	1.7kg (3.7 lbs.)	

## Standard Package/ Optional Accessories



(AT-B2)



Diagonal Eyepiece  
DE16 (AT-B2)



Optical Micrometer  
OM5(F) (AT-B2)



Diagonal Eyepiece  
DE22 (AT-B3/B4)



40x Eyepiece  
EL5 (AT-B2)

- AT-B Level
- Plumb bob
- Hex wrench
- Adjusting pins
- Vinyl cover
- Cleaning cloth
- Lens cap
- User manual
- Hard carrying case

**Your local Authorized Topcon Dealer is:**

Specifications subject to change without notice

©2010 Topcon Corporation All rights reserved. P-69-1